

# Kleeco HARBORHOIST



## STANDARD SPECIFICATIONS POWERED SLING SPACING SYSTEM

MODEL:	SP15H	SP25H	SP35H	SP50H	SP70H	SP85H	SP110H
CAPACITY (TONS)	15	25	35	50	70	85	110
INSIDE CLEAR WIDTH: (STD)	15'	17'	17'	20'	21'	24'	26'
(MAX)	18'	19'	21'	21'	21'	24'	26'
INSIDE CLEAR HEIGHT: (STD)	16'	18'	18'	20'	22'	24'	28'
(MAX)	18'	18'	19'	23'	22'	24'	28'
WHEEL BASE	18'	18'	19'	21'	22'6"	27'	32'
HOIST SPEED (STD FPM)	14	14	14	14	8	8	8
(Max FPM)	24	24	24	24	14	14	14
TRAVEL SPEED (MAX)	180	180	180	180	140	140	140
SLINGS (STD QUANTITY)	2	2	2	2	4	4	4
ADJUSTABLE SLING SETS	2	2	2	2	2	2	2
TIRES (LUG OR RIB)	40X14	40X14	46X16	46X16	50X20	50X20	26.5X25
DRIVE SYSTEM (IN Hub or CHAIN)	EITHER	EITHER	EITHER	EITHER	CHAIN	CHAIN	CHAIN
ENGINE (STD) (CAN QUOTE EQUIVALENT PER CUSTOMER REQUEST)	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	CAT C4.4	CAT C6.6
GRADABILITY (STD)	5.0%	5.0%	5.0%	5.0%	5.0%	5.0%	5.0%
WITH 4WD OPTION	9.25%	9.25%	9.25%	9.25%	9.25%	9.25%	9.25%
STEERING	90DEG	90DEG	90DEG	90DEG	90DEG	90DEG	90DEG
SLING SPACING (STD)	6'-15'	9'-18'	10'-20'	8'-22'	7'-23'	9'-28'	9'-37'
CABLE DROP BELOW GRADE	10'	10'	10'	10'	10'	10'	10'

**Kleeco Serving Marinas and Boatyards for over 40 Years with Quality Engineered Equipment**



**STANDARD SPECIFICATIONS LOAD BAR MANUAL SLING SPACING SYSTEM**

MODEL:	SP20HL	SP30HL	SP40HL	SP50HL	SP60HL	SP80HL
CAPACITY (TONS)	20	30	40	50	60	80
INSIDE CLEAR WIDTH: (STD)	17'	18'	19'	20'	20'	23'
(MAX)	18'	19'	21'	21'	21'	23'
INSIDE CLEAR HEIGHT: (STD)	17'	18'	19'	20'	20'	23'
(MAX)	18'	19'	19'	23'	23'	23'
WHEEL BASE (STD)	18'	20'	20'	21'	22'6"	28'
HOIST SPEED (STD FPM)	14	14	14	14	8	8
(Max FPM)	24	24	24	24	14	14
TRAVEL SPEED (MAX)	180	180	180	180	180	140
SLINGS (STD QUANTITY)	2	2	2	2	4	4
TIRES (LUG OR RIB)	40X14	40X14	46X16	46X16	50X20	50X20
DRIVE SYSTEM (IN Hub or CHAIN)	EITHER	EITHER	EITHER	EITHER	EITHER	CHAIN
ENGINE (STD) (CAN QUOTE EQUIVALENT PER CUSTOMER REQUEST)	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	KUBOTA 3800 DIT	CAT C4.4
GRADABILITY (STD)	5.0%	5.0%	5.0%	5.0%	5.0%	5.0%
WITH 4WD OPTION	9.25%	9.25%	9.25%	9.25%	9.25%	9.25%
STEERING	90DEG	90DEG	90DEG	90DEG	90DEG	90DEG
SLING SPACING (STD)	1'-24'	1'-24'	1'-24'	1'-26'	1'-26'	1'-37'
CABLE DROP BELOW GRADE	10'	10'	10'	10'	10'	10'

**STANDARD FEATURES:**

- \*Fully proportional valving with programmable controls
- \*Programmable accel and decel
- \*Back up mechanical controls
- \*Full size sheaves with grease able bearings
- \*Anti Two-Block System
- \*Fail Safe Brakes
- \*Emissions exceed EPA Regulations
- \*Quality components meeting IP 67 standard

**OPTIONAL FEATURES AND EQUIPMENT:**

- \*Wireless Remote Control Operation
- \*Jib Crane (2500lb max capacity)
- \*Electronic Load Weigh System
- \*Full Time 4WD
- \*Part Time 4WD
- \*4 Wheel Steering
- \*Spreaders and/or additional slings
- \*Lug Tread Tires
- \*Foam Filled Tires
- \*Customized Features to meet Unique Requirements

Lake City Industries, Inc.  
**Kleeco** Marine and Industrial Equipment  
 (800) 483-4868  
[www.kleeco.biz](http://www.kleeco.biz)

**Kleeco** Serving Marinas and Boatyards for over 40 Years with Quality Engineered Equipment